



■ FEATURES

- ▷ Working Pressure : 10kg/cm²
- ▷ Max Temperature : 80 °C
- ▷ Material : JIS G5121 – SCS13
JIS G5121 – SCS14
- ▷ End connection : RF FLANGE
- ▷ TYPE : S.B

■ APPLICABLE STANDARDS

- ▷ Design Rating : JIS B2071
- ▷ Face-to-face Dimensions : JIS B2002
- ▷ End Flange Dimensions : JIS B2220
- ▷ Inspection & Testing : JIS B2003

NO	PARTS NAME	METERIAL
1	NUT	SUS304
2	WASHER	SUS304
3	HANDWHELL	CASTIRON
4	GLAND NUT	SCS13
5	GLAND PACKING	SUS304
6	PACKING	PTFE
7	STEM	SUS304
8	BONNET	SCS13
9	STEM FRAME	SUS304
10	GASKET	PTFE
11	DISC	SCS13/SCS14
12	BODY	SCS13/SCS14

SIZE	D	L	H	D1	D2	D3	Z - M	E
15A	15	80	122	51	70	95	4 – 15	108
20A	20	90	127	56	75	100	4 – 15	108
25A	25	100	132	67	90	125	4 – 19	108
32A	32	110	160	76	100	135	4 – 19	108
40A	40	125	178	81	105	140	4 – 19	125
50A	50	140	210	96	120	155	4 – 19	140
65A	65	170	210	116	140	175	4 – 19	160
80A	80	190	248	126	150	185	8 – 19	180

품질향상을 위하여 사전 예고없이 사양이 변경 될 수 있습니다.